HTE100

Vacuum Tower

with Automatic Filter Cleaning





RUPES HTE100 vacuum tower is a **Dust Extraction System** designed for extracting micro dust during the sanding process.

Thanks to a **high filtration efficiency** and **excellent suction performance**, the unit allows to **work professionally** and to have a **safe** and **clean** working area.

The **RUPES HTE100** is able to support **simultaneously** 2 operators with **high** vacuum and flow rate.

MORE EFFICIENCY COST REDUCTION

HIGH

PERFORMANCE

TECHNICAL DATA	UNIT OF MEASURE	DATA
POWER	[kW/HP]	1,5/2
ELECTRIC SUPPLY	[V]	230V
FREQUENCY	[Hz]	50
PRESSURE SUPPLY	[bar]	6
MAXIMUM VACUUM LEVEL	[mbar]	240
FLOW RATE	[m³/h]	250
FILTERING SURFACE	[m²]	1
TANK CAPACITY	[L]	20
NOISE LEVEL	[dB(A)]	68
USERS	[n]	2
ID VACUUM NOZZLE	[n]	1xD50 [mm] or 2xD34 [mm]
ELECTRIC SOCKETS FOR TOOLS	[n]	2
AIR QUICK COUPLING FOR TOOLS	[n]	2
DIMENSIONS [WxHxD]	[cm]	58x140x45
WEIGHT	[Kg]	120

HTE100

Vacuum Tower

with Automatic Filter Cleaning







SIDE CHANNEL PUMP

A 1,5 [kW] - side channel pump is installed inside the unit. Against simple mobile vacuum cleaner, the pump can work for more than 20.000 hours without maintenance.



PTFE FILTER

A 1 [m²] **PTFE filter** for blocking micro dust particles (99,5% efficiency with 0,3 [µm] dust). PTFE membrane increases filter lifetime also in industrial application with multiple kinds of dusts (dry, humid, metal, plastic, wood, etx.)



ELECTRONIC FRONTAL PANEL

The unit is equipped with an electronic frontal. The side channel pump is started in MANUAL mode or in AUTOMATIC mode when pneumatic tools are





AUTOMATIC FILTER CLEANING SYSTEM

A local compressed air jet cleans all the filter surface and efficiently remove the dust. The main electronic unit automatically activates the system to keep the suction always optimal during the



EASY DUST CONTAINER EXTRACTION

By opening the frontal panel, the dust container can be easily taken from the unit to remove dust. A special lifting rail system makes the operation fast and easy: one only hook is used to fix the dust container.



FRONTAL CONNECTIONS

HTE100 is designed to support 2 users at the same time with:

- n.2 pneumatic/electric connections for tools with auto start;
- Y suction connection for 2 flexible



Via Marconi, 3 A - 20080 Vermezzo (MI) - Italy Tel. +39 - 02.94.69.41 - Fax +39 - 02.94.94.10.40 E-mail: info_rupes@rupes.it - Web: www.rupes.com